



---

**PREPARED BY**

LONESTAR MUNICIPAL EQUIPMENT

Paul Folker - Paul@LonestarME.com

---

**PREPARED FOR**

Kevin Reinartz

City of Farmers Branch  
13333 Davis Court  
Farmers Branch, TX 75234

# QUOTE

**GapVax<sup>®</sup>**



**QUOTE ID**  
24081, MC1510-0655

**UPDATED:**  
3/6/2024



## 2024 MC1510-3S3X COMBINATION JET/VAC

QUOTE ID: 24081, MC1510-0655

April 5, 2024

NOTE: THE GAPVAX MC UNIT MAY EXCEED FEDERAL BRIDGE ALLOWABLE WEIGHTS WHEN LOADED WITH WATER, OR DEBRIS, AND/OR BOTH WATER AND DEBRIS COMBINED. PLEASE CONSULT FACTORY.

	OPTION DESCRIPTION	NOTES	QTY
<b>CHASSIS OPTIONS</b>			
CHA001	<b>CUSTOMER SUPPLIED CHASSIS</b>	MODEL YEAR 2024	1
	SPECIFICATIONS MUST BE APPROVED BY GAPVAX PRIOR TO ORDER. CHASSIS MUST BE PDI COMPLETE PRIOR TO ARRIVAL AT GAPVAX AND MUST BE DELIVERED FULL OF FUEL.	CONSULT FACTORY	
	WHITE CAB COLOR		1
	INFORMATION ONLY, LONE STAR TRUCK CHASSIS VIN: VH7522 (2024 WESTERN STAR, CUMMINS L9 (370 HP ENGINE), ALLISION 3000 RDS TRANSMISSION		1
<b>DEBRIS BODY OPTIONS</b>			
STD	10 USABLE YARD DEBRIS TANK MADE OF 3/16" ASTM A-572 GRADE 50 EXTEN STEEL		STANDARD
STD	FULL-OPENING REAR TAILGATE		STANDARD
STD	STAINLESS STEEL TAILGATE SEALING ROD		STANDARD
STD	FOUR HYDRAULIC REAR DOOR LOCKS		STANDARD
STD	DUAL TAILGATE LIFT CYLINDERS		STANDARD
STD	FRONT MOUNTED HOIST CYLINDER, POWER UP AND DOWN, 55,000 LB CAPACITY		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF BODY		STANDARD
STD	FIVE YEAR WARRANTY ON DEBRIS TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF THE BODY 6' APART		STANDARD
A1	DEBRIS BODY FLUSH OUT SYSTEM		1
A2A	DRAIN AT BOTTOM OF TAILGATE - 6" BRASS LEVER VALVE WITH 15' OF LAYFLAT HOSE	VALVE IS NOT 100% LEAK PROOF	1
A3-CS	FLOAT TYPE LIQUID LEVEL INDICATOR ON SIDE OF DEBRIS TANK		1
A12A	FILTER SCREEN FOR DRAIN VALVE (LONG BOX)	REQUIRES A2	1
A21	CURBSIDE LADDER TO PORT INSPECTION AREA		1
A21B	ADD FOLDING LADDER EXTENSION	REQUIRES A21	1
A18	PURGE VALVE AT GRAVITY DRAIN (1-1/4" BALL VALVE)		1
A22A	GALVANIZED BOLT ON TAILGATE SPLASH SHIELDS		1
A37A	UPGRADE BODY INLET CANNON TO 12" HX STYLE WITH 3" CLEANOUT		1
A44	PNEUMATIC TAILGATE PROP (IN ADDITION TO STANDARD TAILGATE PROP ROD)		1
<b>WATER TANK OPTIONS</b>			
STD	1500 GALLON WATER TANK MADE OF 3/16" 304 STAINLESS STEEL		STANDARD
STD	4" HIGH ANTI-SIPHON RING WITH (4) 2-1/2" HOLES		STANDARD
STD	WATER TANK LEVEL SIGHT TUBE ON CURBSIDE		STANDARD
STD	DRAIN VALVE AT BOTTOM OF WATER TANK		STANDARD
STD	3" FILL LINE WITH 2-1/2" FIRE HOSE CONNECTION CURBSIDE		STANDARD
STD	3" WATER STRAINER WITH STAINLESS STEEL SCREEN ON WATER TANK FILL LINE		STANDARD

STD	3" SUPPLY LINE TO WATER PUMP MOUNTED AT REAR HINGE PIN		STANDARD
STD	FIVE YEAR WARRANTY ON WATER TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS		STANDARD
B6	EXTRA SIGHT TUBE ON DRIVER'S SIDE		1
B23A	GALVANIZED BAFFLES IN THE WATER TANK		1
B30	UPGRADE TO BUTTERFLY VALVE IN 3" SUPPLY LINE		STANDARD
<b>VACUUM SYSTEM OPTIONS</b>			
STD	TRUE 8" DIAMETER VACUUM SYSTEM		STANDARD
STD	VACUUM PUMP DRIVEN VIA MID-SHIP MOUNTED SPLIT SHAFT TRANSFER CASE GEARBOX	(PTO)	STANDARD
STD	NOISE & VIBRATION DAMPENING MOUNTS ON VACUUM PUMP AND TRANSFER CASE		STANDARD
STD	NOISE ATTENUATED VACUUM PUMP DISCHARGE SILENCER WITH RAIN CAP AND DRAIN		STANDARD
STD	24" CENTRIFUGAL CYCLONE SEPARATOR WITH 20" CHAMBER		STANDARD
STD	DUAL STAINLESS STEEL SHUTOFF FLOAT BALLS MOUNTED AT THE REAR OF DEBRIS TANK		STANDARD
STD	STAINLESS STEEL VEE-WIRE SAFETY SCREEN		STANDARD
STD	6" SAFETY VACUUM RELIEF		STANDARD
STD	PANIC SWITCH FUNCTION FOR VACUUM		STANDARD
C8	UPGRADE TO ROOTS TYPE VACUUM PUMP 4,500 CFM AND 18" HG	(4) 18" Hg VACUUM RELIEF VALVES	1
C19	UPGRADE TO XL TRANSFER CASE	9-LITER ENGINE = UP TO 5300 CFM, REQUIRES OPTION C8	1
<b>WATER SYSTEM OPTIONS</b>			
STD	TRI-PLEX WATER PUMP SYSTEM		STANDARD
STD	AIR PURGE SYSTEM FOR PRIMARY CIRCUIT		STANDARD
STD	LOW POINT DRAIN VALVES ON WATER LINES		STANDARD
STD	WASHDOWN CIRCUIT WITH 50' X 1/2" HOSE, QUICK CONNECT, AND WASHDOWN HAND GUN	HOSE REEL NOT INCLUDED	STANDARD
STD	WASHDOWN CIRCUIT(S) WILL INCLUDE A SAFETY FLOW RESTRICTOR (1/4" HOSE)		STANDARD
D25A	HOSE REEL FOR STANDARD WASHDOWN CIRCUIT, 100' X 1/2"		1
D5A	GIANT GP8000 SERIES WATER PUMP RATED AT 63 GPM @ 3000 PSI		1
D-GPVC	VIBRATION DAMPENING COUPLER - WATER PUMP		REQUIRED
D27A	10 GPM / 2,500 PSI HYDRAULICALLY DRIVEN PUMP (COMMON WITH BODY HYDRAULIC SYSTEM)	REQUIRES OPTION J303 HYDRAULIC OIL COOLER	1
D4	UPGRADE TO URACA MULTIFLOW VALVE		1
D4-GUARD	STAINLESS BRANCH GUARD FOR OPTION D4 MULTI-FLOW SAFETY UNLOADER VALVE (MSUV)		1
D21	WATER RECIRCULATION VIA AUTOMATIC TRANSMISSION	JETTER SYSTEM ONLY	1
D4-HX+RA	PNEUMATICALLY OPERATED HX WATER PRESSURE RELIEF VALVE WITH ACTUATED HOSE REEL VALVE (P/N: VAL022790) (G2B)	REQUIRED FOR HX (REPLACES 3-WAY VALVE)	1
D7B	50' X 1/2" HAND GUN REEL FOR HX SYSTEM		1
D18	AIR OUT FOR HX SYSTEM / HX CIRCUIT		1
D35B	1/2" HX LANCE WITH 6' EXTENSION AND RIPS AW NOZZLE		1
D36A	1/2" X 3' LANCE EXTENSION WITH QUICK CONNECTS (CAT022385)		1
D36B	1/2" X 5' LANCE EXTENSION WITH QUICK CONNECTS (CAT022386)		1
<b>BOOM OPTIONS</b>			
STD	8" FRONT MOUNTED TELESCOPING BOOM WITH 26' REACH AND 180 DEG. ROTATION		STANDARD
STD	180 DEGREE POWER ROTATION VIA WORM DRIVE		STANDARD

STD	DUAL 4" LIFT CYLINDERS		STANDARD
STD	CAB PROTECTION RACK		STANDARD
E6	REMOTE LUBE FOR BOOM LIFT AND ROTATION		1
E7	3/16" HEAVY DUTY BOOM ELBOW WITH 6" FORMED CHANNEL RADIUS		1
<b>HOSE REEL OPTIONS</b>			
STD	FRONT FRAME MOUNTED HOSE REEL WITH 180 DEGREE ARTICULATION		STANDARD
STD	HOSE REEL RATED FOR 800' OF HOSE AND 3,000 PSI		STANDARD
STD	EXTERIOR HOSE EXPANSION RIBS		STANDARD
F1C	DIGITAL FOOTAGE COUNTER - SHAFT-MOUNTED		1
F11	AUTOMATIC HOSE LEVEL WINDER (INCLUDES "J-HOOK" STLYE HOSE GUIDE)		1
<b>CONTROLS, GAUGES, ACCESSORIES OPTIONS</b>			
STD	CAB-MOUNTED AIR SHIFT CONTROLS FOR BLOWER, HYDRAULICS, AND WATER PUMP		STANDARD
STD	CONTROL PANEL MOUNTED AT FRONT HOSE REEL		STANDARD
STD	OPERATOR CONTROL PANEL INCLUDES GAUGES FOR ENGINE, HYDRAULICS, VACUUM, AND WATER PUMP		STANDARD
STD	PANIC SWITCH TO RELIEVE WATER PRESSURE AND VACUUM ON FRONT PANEL AND CURB SIDE OF UNIT		STANDARD
G2B	G2B CONTROL SYSTEM WITH DM430 DISPLAY INCLUDES:	<b>WIRELESS NOT INCLUDED, SELECT OPTION G19 OR G21</b>	1
	LOW WATER SHUTDOWN PROTECTION		1
	HIGH WATER TEMPERATURE SHUTDOWN PROTECTION		1
	ENGINE OVERSPEED PROTECTION		1
	ON-SCREEN DIAGNOSTICS FOR WATER, PTO AND ENGINE LEVELS		1
G4A	HIGH DEBRIS LEVEL LIGHT & ALARM WIRED TO VACUUM RELIEF	REQUIRES A3	1
G6	BLOWER TEMPERATURE GAUGE WIRED TO VACUUM RELIEF	<b>NOT AVAILABLE WITH OPTION C17</b>	1
G21A	WIRELESS REMOTE WITH BOOM, VACUUM AND FRONT HOSE REEL WATER ON/OFF		1
G21-TD	UPGRADE TO AARCOMM TRIDENT REMOTE	REQUIRES OPTION G21	1
G21-AWR	ADDITIONAL WIRELESS TRANSMITTER	REQUIRES OPTION G19 OR G21	1
<b>LIGHTING</b>			
STD	TRUCK-LITE LED RUNNING (MARKER) LIGHTS		STANDARD
STD	LED STOP/TAIL/TURN LIGHT WITH POLISHED STAINLESS STEEL BOXES		STANDARD
H1	ONE LED STROBE BEACON LIGHT - FRONT ( <b>SAE CLASS-1</b> (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	1
H2	ONE LED STROBE BEACON LIGHT - REAR ( <b>SAE CLASS-1</b> (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	1
H5B	(2) BOOM WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429)		1
H6B	(2) REAR WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429)		1
H7BC	(4) SIDE WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) (2 PER SIDE)		1
H38	CORDLESS RECHARABLE LED LIGHT		1
H15C	WHELEN ION SUPER LED FLASHERS - 8 LIGHT HEADS		1
	2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE REAR		1
H22	REAR ARROW LIGHT - LOW PROFILE LED ARROW STICK ( <b>CLASS-1</b> (SAE J595))	WHELEN TAM85 OR EQUAL	1
<b>STORAGE OPTIONS</b>			
STD	25' FIRE HOSE BASKET		STANDARD
I6D-DS	STAINLESS STEEL, 30" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE DRIVER'S SIDE		1

I9C	48" TOOL BOX - STAINLESS STEEL, 48" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE		1
I25C	TUNNEL TOOLBOX - STAINLESS STEEL, 30" HIGH X 24" WIDE X 50" DEEP	CONSULT ENGINEERING	1
I10	HAND GUN HOLDER - TOP OF CURBSIDE TOOL BOX		1
I14	TRAFFIC CONE HOLDER ON DRIVER'S SIDE		1
I15	WATER COOLER HOLDER WITH 5 GALLON COOLER		1
I17B	NOZZLE RACK - SIX (6) NOZZLES, 3/4"		1
I20A	REAR DRAIN HOSE RACK FOR 6" LAYFLAT HOSE X 15' LONG		1
I22	UPGRADE TUBE TRAYS TO POLISHED STAINLESS STEEL		1
I26C	TWO BUMPER TOOL BOXES - STAINLESS STEEL, 16" HIGH X 12" WIDE X 18" DEEP WITH FOLD DOWN DOOR		1
<b>CHASSIS OPTIONS</b>			
STD	DOT LIGHTING / FENDERS / MUD FLAPS / TAILGATE SAFETY PROP, ICC LIGHTS		STANDARD
STD	REMOTE ACTUATED BODY SAFETY PROP		STANDARD
STD	70 GALLONS AW-46 HYDRAULIC OIL, LEVEL/TEMPERATURE GAUGE, SHUTOFF ON SUCTION		STANDARD
STD	REAR BUMPER, TRIANGLE KIT, FIRE EXTINGUISHER, BACKUP ALARM		STANDARD
STD	ALLISON 10-BOLT PTO UPGRADE		STANDARD
J000	MID-SHIP MOUNTED (SPLIT-SHAFT) TRANSFER CASE WITH TOP DISCONNECT		1
J0	FRONT BUMPER		1
J2	TRANSFER CASE OIL LEVEL SIGHT GLASS / FILL, MOUNTED ON DRIVER'S SIDE FRAME RAIL (PN: GAU006456)		1
J3	TOW HOOKS FRONT		1
J4B	TOW HOOKS REAR - FRAME MOUNTED		1
J12	METAL MUD FLAPS IN FRONT OF REAR TIRES		1
J303	ADD HYDRAULIC OIL COOLER TO CIRCUIT	<b>REQUIRED WITH OPTION D301* OR OPTION D27*</b>	1
<b>PAINT OPTIONS</b>			
STD	PAINTED WITH PPG URETHANE PAINT		STANDARD
STD	PAINT BODY WHITE		STANDARD
STD	PAINT FRAME AND PARTS BLACK		STANDARD
STD	PAINT HOSE REEL AND BOOM BLACK		STANDARD
STD	FLEET FINISH		STANDARD
K6	CONSPICUITY REFLECTIVE TAPE		1
<b>MISCELLANEOUS OPTIONS</b>			
STD	25 FEET OF VACUUM TUBING (5) AND CLAMPS		STANDARD
STD	TIGER TAIL HOSE GUIDE		STANDARD
STD	TWO SEWER CLEANING NOZZLES		STANDARD
M3	FILL HOSE 25' X 2 1/2"		1
M9I	3/4" PIRANHA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022499)		1
M15	ADDITIONAL OPERATIONS AND MAINTENANCE MANUAL - EACH		1
M29C	THREE CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR AND TWO (2) DVR-920 SIDE CAMERAS. SIDE CAMERAS TO		1
M34	ADDITIONAL 8" X 5' ALUMINUM VACUUM TUBE (P/N: PIP008549)		2
M35	ADDITIONAL 8" TUBE CLAMP, EACH (P/N: CLA000978)		2
M37	HEAVY DUTY ALUMINUM HX TUBE, 8" X 5' X 0.090" WALL WITH PRESSED IN STEEL ENDS AND SOFT TIP END (P/N: PIP008550 & GAS023037)		1
<b>CUSTOM OPTIONS</b>			

**	MATERIALS SURCHARGE	(EFFECTIVE MAY 1, 2022)	1
**	***NOTE: H15C BODY-MOUNTED LIGHT HEADS TO BE BLUE/AMBER WITHIN EACH LIGHT HEAD		1
*	LME SUPPLIED SEWER NOZZLE PACKAGE, INCLUDES: ARROW w/ DRILL POINT, REVOLUTION, TYPHOON, STEALTH, 6-JET FLOUNDER, & MARKSMAN NOZZLES		1
**	LME SUPPLIED - 3/4" X 20' LEADER HOSE		1
***	***LME Supplied - 4" HOSE ADAPTER THINGY WITH 8" MBL		1
*****	***LME Supplied - Trip for 4 City of Farmers Branch employees to GapVax in Johnstown, PA for a Pre-Delivery inspection		1



## PRICING SUMMARY

<b>PRICE OF BASE UNIT WITH OPTIONS:</b>	<b>\$ 425,455.00</b>
<b>DISCOUNT:</b>	<b>\$ 16,015.00</b>
<b>DELIVERY:</b> (\$1,000.00 MINIMUM) @ <b>\$4.00 PER MILE</b>	<b>\$ 5,560.00</b>
<b>ESTIMATED SUBTOTAL:</b>	<b>\$ 415,000.00</b>
<b>SALES TAX:</b>	<b>\$ -</b>
<b>FEDERAL EXCISE TAX (BODY):</b>	<b>\$ -</b>
<b>FEDERAL EXCISE TAX (CHASSIS):</b>	<b>\$ -</b>
<b>TOTAL PRICE (PER UNIT):</b>	<b>\$ 415,000.00</b>

**ALL PRICES ARE IN US DOLLARS**

ALL ORDERS ARE SUBJECT TO CURRENT PRICES IN EFFECT AT THE TIME OF ORDER ACKNOWLEDGMENT. PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. PRICING DISCLAIMER: WHILE WE MAKE EVERY EFFORT TO MAINTAIN AND PRESERVE PRICING ACCURACY, ALL COST INCREASES INCURRED AFTER ORDER ACKNOWLEDGMENT FOR MAJOR COMPONENTS AND GOVERNMENT MANDATED REQUIREMENTS, TARIFFS, AND RAW MATERIAL SURCHARGES WILL BE PASSED THROUGH AND ADDED TO CUSTOMER INVOICES WITH OR WITHOUT NOTICE. ALTHOUGH THE INFORMATION ON THIS QUOTATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AT THE TIME OF PRINTING, WE MAKE NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THIS INFORMATION. WE RESERVE THE RIGHT TO CHANGE, DELETE, OR OTHERWISE MODIFY THE PRICING INFORMATION WHICH IS REPRESENTED HEREIN WITHOUT ANY PRIOR NOTICE. WE CAREFULLY CHECK PRICING SPECIFICATIONS, BUT OCCASIONALLY ERRORS CAN OCCUR, THEREFORE WE RESERVE THE RIGHT TO CHANGE SUCH PRICES WITHOUT NOTICE. WE DISCLAIM ALL LIABILITY FOR ANY ERRORS OR OMISSIONS IN THE MATERIALS. IN NO EVENT WILL WE BE RESPONSIBLE FOR ANY DAMAGES OF ANY NATURE WHATSOEVER FROM THE RELIANCE UPON INFORMATION FROM THESE MATERIALS. PLEASE CHECK YOUR ORDER TO CONFIRM YOUR PRICING INFORMATION

IF THE CUSTOMER SUPPLIED CHASSIS IS REGISTERED WITH A PERMANENT LICENSE PLATE AT THE TIME OF PICK-UP OF THE COMPLETED UNIT AT THE GAPVAX FACTORY IN JOHNSTOWN, PA, THEN GAPVAX INC. IS OBLIGATED TO COLLECT A 6% PENNSYLVANIA STATE SALES TAX ON THE VACUUM UNIT / MODULE. IF SALES TAX EXEMPT, EXEMPTION FORM MUST BE SUPPLIED. DOES NOT APPLY TO A COMPLETED UNIT WITH TEMPORARY REGISTRATION TAG (CARDBOARD TAG) AT THE TIME OF PICK-UP OR TO A COMPLETED UNIT DELIVERED BY GAPVAX TO AN OUT OF PENNSYLVANIA END DESTINATION.

DELIVERY TERMS: TERMS OF DELIVERY SHALL BE F.O.B. SHIPPING POINT, JOHNSTOWN, PENNSYLVANIA, U.S.A. THIS PROPOSAL WILL REMAIN IN EFFECT FOR 30 DAYS, UNLESS CHANGED IN THE INTERIM UPON WRITTEN NOTICE FROM THE COMPANY. PLEASE RETURN ONE SIGNED COPY OF THIS PROPOSAL, AND ANY FUTURE CORRESPONDENCE TO: GAPVAX, INCORPORATED, 575 CENTRAL AVE., JOHNSTOWN, PA 15902. BY SIGNING THIS PROPOSAL, PURCHASER THEREBY EXPRESSES ACCEPTANCE OF EACH AND EVERY TERM AND CONDITION SET FORTH HEREIN. ANY PURCHASE ORDER OR ACKNOWLEDGMENT OFFERING TERMS INCONSISTENT WITH THE TERMS AND CONDITIONS HEREOF SHALL HAVE NO BINDING EFFECT WHATSOEVER ON GAPVAX INCORPORATED (THE "COMPANY") OR THE TERMS AND CONDITIONS HEREOF. THIS DOCUMENT AND THE OTHER DOCUMENTS SPECIFICALLY REFERRED TO AS BEING A PART HEREOF, CONSTITUTE THE ENTIRE CONTRACT ON THE SUBJECT MATTER, AND SHALL NOT BE MODIFIED EXCEPT IN WRITING SIGNED BY BOTH PARTIES. ASSIGNMENT MAY BE MADE ONLY WITH WRITTEN CONSENT OF THE OTHER PARTY.

SIGNATURE \_\_\_\_\_

DATE \_\_\_\_\_

Please return a signed copy to [Paul@LonestarME.com](mailto:Paul@LonestarME.com)

**Chassis and Demo Units are SUBJECT TO PRIOR SALE**

**QUOTE ID**  
24081, MC1510-0655

**LAST UPDATED:**  
3/6/2024